Bradnam's

hinged doors





The Bradnam's Difference



essential range

Key Features and Benefits

- The traditional style makes a classical addition to modern homes
- Complement with side lites and hi lites to create a striking design feature
- Suitable in areas with restricted opening space, such as small balconies
- No exposed sharp edges, reducing the chance of injury
- Optional Parliament hinges allow doors to be opened 180 degrees, protecting pedestrians
- Optional 4 point lever compression lock for superior security

Performance Parameters

Frame size	100mm
Maximum door height	2450mm
Maximum door width	1936mm
Maximum panel width	1000mm
Maximum panel weight	50kg
Maximum water rating	600pa (open out only) (single leaf only)
Maximum wind rating	4000Pa ULS
Maximum glass thickness	12.38mm (single glazed) 24mm (IGUs)
Maximum bushfire rating	BAL 40



signature range

Key Features and Benefits

- A clean, contemporary refinement of a classic style
- Complement with side lites and hi lites to create a striking design feature
- Suitable in areas with restricted opening space, such as small balconies
- No exposed sharp edges, reducing the chance of injury
- Security and insect screen options easily installed within the frame
- Optional 4 point lever compression lock for superior security

Performance Parameters

Frame size	125mm
Maximum door height	2450mm
Maximum door width	1936mm
Maximum panel width	1000mm
Maximum panel weight	50kg
Maximum water rating	150pa (single leaf only)
Maximum wind rating	4000Pa ULS
Maximum glass thickness	12.38mm (single glazed) 24mm (IGUs)
Maximum bushfire rating	BAL 40




commercial range

Key Features and Benefits

- Heavy duty 50mm sash for superior strength and rigidity
- Compatible with a range of architectural hardware
- Rails are 50mm deep to match stile depth for a consistent appearance
- Stainless steel fastenings minimises the chance of corrosion
- Dead lock for superior security as standard

Performance Parameters

Frame size	100mm
Maximum door height	2700mm
Maximum door width	2000mm
Maximum panel width	1000mm
Maximum panel weight	80kg
Maximum glass thickness	13.52mm (single glazed) 24mm (IGUs)
Maximum acoustic rating	Rw35
Maximum bushfire rating	BAL 40





commercial range hardware



The hardware displayed on this page are a guide only and due to the nature of printing processes, some degree of colour and gloss variations may occur. Bradnam's Windows & Doors recommend the viewing of an actual hardware product prior to order.





Bradnam's products are proudly made in Australia and designed specifically to meet all Australian conditions Note: Products may be subject to local variation, regulatory requirements and confirmation of structural performance. The Signature range is only available as an Open In configuration.













For more information call Bradnam's on 1300 WINDOWS 1300 946369 or visit bradnams.com.au