

Bradnam's

awning windows



Bradnam's
windows & doors

The Bradnam's Difference



essential range

Key Features and Benefits

- Natural ventilation (even during light rain) thanks to the windows' top hinged configuration
- Curtain-friendly design options with folding handles to limit interference with curtains
- Security and insect screens installed within the frame to keep out bugs and intruders without compromising access to the winder
- Architectural symmetry with other Bradnam's windows and doors for a holistic look and feel
- Twin chain options for ease of operation for larger windows
- Long-lasting santoprene seals providing superior protection against the elements

Performance Parameters

Frame size	52mm
Maximum panel height	2150mm / 2400mm ^A
Maximum panel width	2150mm ^B
Maximum panel weight	74kg ^D
Maximum water rating	600pa
Maximum wind rating	4500Pa ULS
Maximum glass thickness	12.76mm (single glazed) 24mm (IGUs)
Maximum bushfire rating	BAL 40

A Single 'A' configuration only

B Without cam handles

D Friction stays only



signature range

Key Features and Benefits

- Maximised 'picture frame' views with a large glass area and mitre joints
- Smart design, including 100mm frames allowing the hardware and security/insect screens to be installed within the frame
- Superior stability and strength thanks to 100mm frames and sashes hung from a concealed heavy duty bar
- Superior materials including stainless steel chain to minimise corrosion, and Santoprene seals designed to withstand harsh weather conditions
- Safety-focused design with no sharp edges, and optional opening restrictions
- Optional features including folding handles to limit interference with curtains and keyed locks for security

Performance Parameters

Frame size	100mm
Maximum panel height	2400mm
Maximum panel width	2150mm ^A
Maximum panel weight	74kg ^B
Maximum water rating	600Pa
Maximum wind rating	4500Pa ULS
Maximum glass thickness	12.76mm (single glazed) 24mm (IGUs)
Maximum bushfire rating	BAL 40

A Without Cam handles

B Friction stays only

commercial range

Key Features and Benefits

- 'Picture frame' look perfect for commercial settings
- Large glass area to maximise natural daylight and the view – both inside and out
- Safety-first design with no sharp edges, and optional opening restrictions to reduce the chance of injury
- Weatherproof design with stainless steel chain and Santoprene seals
- Smart design options including folding handles to limit interference with curtains and twin chains for operating larger sashes
- Internal glazing options available allow windows to be re-glazed internally

Performance Parameters

Frame size	100mm
Maximum panel height	2400mm
Maximum panel width	2150mm ^A
Maximum panel weight	74kg ^B
Maximum water rating	600Pa
Maximum wind rating	4500Pa ULS
Maximum glass thickness	12.76mm (single glazed) 24mm (IGUs)
Maximum acoustic rating	Rw34
Maximum bushfire rating	BAL 40

A Without Cam handles

B Friction stays only

awning window hardware

essential | signature
commercial

Single chain winder

Standard handle shown

Upgrade handle

Handle can be folded to minimise interference with blinds and curtains



Twin chain winder

Standard handle shown

Handle can be folded to minimise interference with blinds and curtains



The hardware displayed on this page are a guide only and due to the nature of printing processes, some degree of colour and gloss variations may occur. Bradnam's Windows & Doors recommend the viewing of an actual hardware product prior to order.

windows | doors | insect & safety screens | showerscreens | mirrors & wardrobes



Australian
Owned & Made

Bradnam's products are proudly made in Australia and designed specifically to meet all Australian conditions



Note: Products may be subject to local variation, regulatory requirements and confirmation of structural performance

For more information call Bradnam's on
1300 WINDOWS 1300 946369
or visit bradnams.com.au

Bradnam's
windows & doors

Bradnam's Windows and Doors, QBCC Act lic 58885 | © Bradnam's Windows and Doors Jan 2016